




The VAPOR[®] 55 MX all-electric helicopter unmanned aircraft system (UAS) is extremely versatile and can be easily configured to support a variety of mission requirements for defense, commercial and industrial applications. The all-weather VAPOR UAS incorporates a modular design that makes integration of high-performance single or multiple sensor payloads quick and easy. It features a sleek, modular, low-profile design that is rugged and portable with its telescoping tail and fold-up landing gear. Specifically built for heavier payloads and longer distances, VAPOR is unmatched by any quadcopter or other helicopter UAS with its 24-pounds of flexible payload capacity, and up to 105 minutes of endurance with a 3rd battery option.

Built for Heavier Payloads & Longer Distances



- > Sleek, modular airframe design for easy assembly & disassembly
- Flexible core architecture-key enabler for continuous development > that will allow for seamless extensions & upgrades
- > Modular radio options—seamlessly operate with a low-cost encrypted radio or swap to hardened military radio

_Specifications

OPTICAL SENSOR	Trillium HD-25 (standard), Other options HD-45-LV-CZ, HD-45-CZ-GS, HD-55-LV- CZ, HD-55-MV HD, HD-25-LV
GROUND SPEED LIMIT	33 mph (15 m/s)
DIMENSIONS	Aircraft: 6 ft x 2.2 ft x 2.1 ft (1.8 m x 0.67 m x 0.64 m) // Rotor Diameter: 7.5 ft (2.29 m)
OPERATING ALTITUDE	0–12,000 ft (3,657 m) MSL (density)
ENVIRONMENTAL OPERATIONAL LIMITS	Min: 0 °F (-17 °C) // Max: 120 °F (49 °C)
MAX WIND PEAK	Sustained: 34.5 mph (30 kts)
DATA LINKS	900 MHz, 2.4 GHz or 5.89 GHz (video), Persistent Systems MPU5 (Standard), options Silvus, DTC
GROUND CONTROL	Live GPS position, full authority control, automatic or manual flight

3. With HD-25-up to a 15-18 lbs droppable payload



HARDCASE PACK OUT 12.9 in height x 16.1 in depth x 45.5 in width



RUCKSACK PACK OUT 25 in height x 9.5 in depth x 14.3 in width

AV - ph: 703.418.2828 - www.avinc.com // @ 2025 AeroVironment, its product names and the AV logo are protected trademarks of AeroVironment, Inc. All other company, product names, logos, and brands are property of their respective owners and are for identification purposes only. Use of these names, logos, and brands does not imply endorsement. Screen images may be simulated. All specifications are subject to change. This data sheet consists of AeroVironment, Inc. general capabilities information that does not contain controlled technical data as defined within the International Traffic in Arms Regulations (ITAR) Part 120.10 or Export Administration Regulations (EAR) Part 734.7-11.

